



LENGTH TOLERANCE:

LENGTH (L)	TOLERANCE
≤ 3M	+150MM/-0
> 3M/≤ 30M	+300MM/-0
> 30M	+1%/-0

ITEMS#	DESCRIPTION	QTY
1	SC/APC CONNECTOR BLUE HOUSING AND OFF BLUE BOOTS	192
2	96 FIBER DISTRIBUTION CABLE SM YELLOW	L
3	HEAT SHRINK TUBING(L:100mm)	2
4	SUB-UNIT LABELS	16
5	HEAT SHRINK TUBING(L:50mm)	16

FIBER COLOR CODE FOR SUBUNITS:

COLOR CODE	SUBUNIT 1	SUBUNIT 2	SUBUNIT 3	SUBUNIT 4	SUBUNIT 5	SUBUNIT 6	SUBUNIT 7	SUBUNIT 8
	FIBER	FIBER	FIBER	FIBER	FIBER	FIBER	FIBER	FIBER
BLUE	1	13	25	37	49	61	73	85
ORANGE	2	14	26	38	50	62	74	86
GREEN	3	15	27	39	51	63	75	87
BROWN	4	16	28	40	52	64	76	88
SLATE	5	17	29	41	53	65	77	89
WHITE	6	18	30	42	54	66	78	90
RED	7	19	31	43	55	67	79	91
BLACK	8	20	32	44	56	68	80	92
YELLOW	9	21	33	45	57	69	81	93
VIOLET	10	22	34	46	58	70	82	94
ROSE	11	23	35	47	59	71	83	95
AQUA	12	24	36	48	60	72	84	96

SPECIFICATIONS:

Type	Single Mode
	UPC
Insertion Loss	≤0.3dB
Return Loss	≥50dB
Test Wavelength	1310nm