



TYPE	RATING	A		B		C	D	E	F	G	H	RECOMMENDED WIRE SIZE
		3P	4P	3P	4P							
T3019	30A	59	71	49	61	34	21	12	9.5	M4	4.5	3.5mm <sup>2</sup>
T3011	60A	85	104	73	92	52	34	19	15.5	M6	5.5	14mm <sup>2</sup>
T3015	100A	99	122.5	87	110.5	60	38	23.5	20	M8	5.5	38mm <sup>2</sup>
T3013	150A	109.5	137.5	97.5	125.5	70	44	28	24	M8	5.5	60mm <sup>2</sup>
T3014	200A	133	168	119.5	154.5	83	55	35	30	M10	6.5	100mm <sup>2</sup>
T3017	300A	211	270	193	252	110	62	59	52	M12	6.5	150mm <sup>2</sup>
T3018	400A	211	270	193	252	110	62	59	52	M12	6.5	150mm <sup>2</sup>
RT 600-11	600A	243.4	309	223	289	124	78	66	52	M12	8.5	325mm <sup>2</sup>
RT 800-11	800A	243.4	309	223	289	124	78	66	52	M16	8.5	200mm <sup>2</sup> X2
RT 1000-11	1000A	243.4	309	223	289	124	78	66	52	M16	8.5	325mm <sup>2</sup> + 200mm <sup>2</sup>