

MULTIPLE OUTPUT LINEAR D.C. POWER SUPPLY



GPS-2303/3303/4303



Patent No: ZL 02 3 35264 . 7

POWER SUPPLIES

FEATURES

- * 2, 3 and 4 Independent Isolated Output
- * Four "3 Digits" LED Displays
- * 0.01% Load and Line Regulation
- * Low Ripple and Noise
- * Tracking Operation and Auto Series/Parallel Operation
- * Output ON/OFF Switch
- * Output Voltage and Current Setting When Output Disable (Except for GPS-2303)
- * Fan Speed Control Circuit to Minimize Fan Noise
- * Over Load and Reverse Polarity Protection

GPS-001 Voltage/Current protection Knob



Rear Panel



GPS-3303

The GPS-Series are 2-4 channel, 180 to 200W output, linear DC power supplies. Overload and reverse polarity protection and an output on/off switch keep the GPS-Series and their load safe from unexpected conditions. A High regulation (0.01%+3mV) and low ripple/noise (< 1mVrms, 5Hz~1MHz) are maintained for channel 1 and 2 in constant voltage mode. Automated cooling fan speed control minimizes fan noise according to load conditions, ensuring quiet operation. The GPS-Series are an ideal solution for lightweight, inexpensive bench-top or portable applications requiring high regulation and multiple outputs.

SPECIFICATIONS

	GPS-4303				GPS-3303		GPS-2303										
OUTPUT MODE	CH1	CH2	CH3	CH4	CH1	CH2	CH3	CH1	CH2								
Voltage	0 ~ 30V	2.2 ~ 5.2V	8 ~ 15V	0 ~ 30V	5V Fixed		0 ~ 30V										
Current	0 ~ 3A	1A Max.	1A Max.	0 ~ 3A	3A Max.		0 ~ 3A										
Tracking Series Voltage	0 ~ 60V				0 ~ 60V		0 ~ 60V										
Tracking Parallel Current	0 ~ 6A				0 ~ 6A		0 ~ 6A										
CONSTANT VOLTAGE OPERATION (CH1, CH2)																	
Line Regulation	$\leq 0.01\% + 3\text{mV}$		$\leq 0.01\% + 3\text{mV}$ (rating current $\leq 3\text{A}$)		$\leq 0.02\% + 5\text{mV}$ (rating current $> 3\text{A}$)		$\leq 1\text{mVrms}, 5\text{Hz} \sim 1\text{MHz}$										
Ripple & Noise	$\leq 100\mu\text{s}$ (50% Load change, Minimum load 0.5A)																
CONSTANT CURRENT OPERATION (CH1, CH2)																	
Line Regulation	$\leq 0.2\% + 3\text{mA}$		$\leq 0.2\% + 3\text{mA}$		$\leq 3\text{mA rms}$												
TRACKING OPERATION (CH1, CH2)																	
Tracking Error	$\leq 0.5\% + 10\text{mV}$ of CH1		$\leq 0.01\% + 5\text{mV}$		$\leq 300\text{mV}$		$\leq 2\text{mVrms}, 5\text{Hz} \sim 1\text{MHz}$										
Series Regulation																	
Load Regulation																	
Ripple & Noise																	
CH3 OPERATION (for GPS-3303/4303)																	
CH3 Voltage	GPS-4303 : 2.2V ~ 5.2V , GPS-3303 : 5V Fix																
Line Regulation	$\leq 5\text{mV}$		$\leq 15\text{mV}$														
Load Regulation	$\leq 10\text{mV}$		$\leq 2\text{mVrms}, 5\text{Hz} \sim 1\text{MHz}$														
Ripple & Noise																	
Current Output	GPS-4303 : 1A, GPS-3303 : 3A																
CH4 OPERATION (for GPS-4303)																	
CH4 VOLTAGE	8V ~ 15V		$\leq 5\text{mV}$		$\leq 10\text{mV}$		$\leq 2\text{mVrms}, 5\text{Hz} \sim 1\text{MHz}$										
Line Regulation	$\leq 5\text{mV}$		$\leq 10\text{mV}$														
Load Regulation	$\leq 10\text{mV}$		$\leq 2\text{mVrms}, 5\text{Hz} \sim 1\text{MHz}$														
Ripple & Noise																	
Current Output	1A																
METER																	
Digital	3 digits 0.5" LED display		GPS-4303/3303 Out ON Accuracy $\pm (0.5\% \text{ of rdg} + 2\text{ digits})$		GPS-4303/3303 Out OFF Accuracy $\pm (0.5\% \text{ of rdg} + 8\text{ digits})$		GPS-2303 Accuracy $\pm (0.5\% \text{ of rdg} + 2\text{ digits})$										
INSULATION																	
Chassis and Terminal	$\geq \text{DC } 500\text{V} / 20\text{M}\Omega$				$\geq \text{DC } 500\text{V} / 30\text{M}\Omega$												
Chassis and AC Cord																	
POWER SOURCE																	
AC 100V/120V/220V $\pm 10\%$, 230V(+10%~-6%), 50/60Hz																	
DIMENSIONS & WEIGHT																	
255(W) x 145(H) x 265(D) mm, Approx. 7 kg																	

ORDERING INFORMATION

GPS-4303 4-channels, 200W D.C. Power Supply

GPS-3303 3-channels, 195W D.C. Power Supply

GPS-2303 2-channels, 180W D.C. Power Supply

ACCESSORIES :

User manual x 1, Power cord x 1,

GPS-4303:Test lead GTL-104 x 2,GTL-105 x 2 ; European test lead GTL-203 x 2,GTL-204 x 2, GTL-201A x1

GPS-3303:Test lead GTL-104 x 2,GTL-105 x 1 ; European test lead GTL-203 x 1,GTL-204 x 2, GTL-201A x1

GPS-2303:Test lead GTL-104 x 2 ; European test lead GTL-204 x 2, GTL-201A x1

OPTIONAL ACCESSORIES

GPS-001 Voltage/Current Protection Knob (It's available OCT/07' production batch)