

N Male  
F4PNMV2-H




N Female Bulkhead  
F4PNF-BH



UHF Male  
44ASP



N Male Right Angle  
F4PNR-H



7/8" EIA  
44ASR



7-16 DIN Female  
F4PDF-C



7-16 DIN Male  
F4PDMV2-C

### Connectors

Interface	Description	Type Number	Inner Contact Attachment	Outer Contact Attachment	Plating Code	Max. Length in (mm)	Max. Dia. in (mm)
N Male	Hex Head	<b>F4PNMV2-H</b>	Solder	Crush-Flare	SG	2.13 (54.0)	0.94 (23.8)
N Male	Hex Head	<b>F4PNMV2-HC</b>	Captivated	Crush-Flare	SG	2.13 (54.0)	0.94 (23.8)
N Male	Rt Angle, Hex Hd	<b>F4PNR-H</b>	Solder	Tab-Flare	SG	3.3/1.5 (84/38)	0.86 (21.8)
N Male		<b>F4PNR-HC</b>	Captivated	Crush-Flare	SG	2.8 (71.9)/1.6 (41.5)	1 (25.7)
N Female	–	<b>F4PNF</b>	Solder	Self-Flare	SG	2.3 (53.3)	0.88 (22.4)
N Female	–	<b>F4PNF-C</b>	Captivated	Self-Flare	SG	2.3 (53.3)	0.88 (22.4)
N Female	Bulkhead	<b>F4PNF-BH</b>	Solder	Self-Flare	SG	2.3 (58)	0.95 (24.1)
4.1/9.5 DIN Male	–	<b>F4PKM-C</b>	Captivated	Self-Flare	SS	2.0 (50)	0.95 (24.1)
4.1/9.5 DIN Male	Rt Angle, Outdoor Use	<b>F4PKR-C</b>	Captivated	Self-Flare	SS	2.3/1.5 (57/38)	0.95 (24.1)
7-16 DIN Male	–	<b>F4PDMV2-C</b>	Captivated	Crush-Flare	SS	1.98 (50.2)	1.05 (26.7)
7-16 DIN Male	–	<b>F4PDMV2</b>	Solder	Crush-Flare	SS	2.10 (53.4)	1.05 (26.7)
7-16 DIN Male	Right Angle	<b>F4PDR</b>	Solder	Self-Flare	SS	2.4/1.8 (61/46)	1.4 (35.6)
7-16 DIN Male	Right Angle	<b>F4PDR-C</b>	Captivated	Self-Flare	SS	2.1/2.0 (53/50)	1.4 (35.6)
7-16 DIN Female	–	<b>F4PDF-C</b>	Captivated	Self-Flare	SS	2.0 (50)	1.1 (27.9)
7-16 DIN Female	–	<b>F4PDF</b>	Solder	Self-Flare	SS	2.0 (50)	1.1 (27.9)
7-16 DIN Female	Bulkhead	<b>F4PDF-BH</b>	Solder	Self-Flare	SS	2.01 (51.1)	1.50 (38)
7-16 DIN Female	Panel Mount	<b>F4PDF-PM</b>	Solder	Self-Flare	SS	2.01 (51.1)	1.26 (32)
7-16 DIN Female	Bulkhead	<b>F4PDF-BHC</b>	Captivated	Self-Flare	SS	2.0 (50)	1.8 (45.7)
7-16 DIN Female	Panel Mount	<b>F4PDF-PMC</b>	Captivated	Self-Flare	SS	2.0 (50)	1.3 (33)
7/8" EIA Flange	–	<b>44ASR</b>	Solder	Tab-Flare	BS	3.3 (84)	1.4 (35.6)
UHF Male	–	<b>44ASP</b>	Solder	Tab-Flare	BS	2.1 (53)	0.84 (21.3)
UHF Female	–	<b>44ASU</b>	Solder	Tab-Flare	BS	2.3 (58)	0.84 (21.3)
HN Male	–	<b>44ASJ</b>	Solder	Tab-Flare	BB	2.4 (61)	0.84 (21.3)
SC Male	–	<b>44SPCW</b>	Solder	Tab-Flare	SG	2.7 (69)	0.88 (22.4)

**Plating Codes:** BB - Brass Body and Pin, BS - Brass Body and Silver Plated Pin, SG - Silver Plated Body and Gold Plated Pin, SS - Silver Plated Body and Pin

**Connector Accessories** – See page 624

**Factory Attached Connectors** – For factory made cable assemblies and jumper cables, see pages 584-587.