

LC UPC to FC UPC Duplex PVC/LSZH/OFNP 9/125 Single Mode Fiber
Patch Cable

SM-LCU-FCU-DX-FS



Description

The 9/125 μ m single mode fiber patch cable meets RoHS compliant, and all cables are 100% optically tested for insertion loss to ensure high quality, it is very cost-effective for network cabling.

Fiberstore also provides a full set of OEM services, such as fiber connector, length, color, fiber grade, specification, material, package etc.

Specifications

Connector	LC to FC	Jacket OD	standard 2.0 (default)/3.0mm
Fiber Mode	9/125 μ m	Jacket Color	Yellow
Polish	UPC to UPC	Wavelength	1310/1550nm
Fiber Type	Duplex	Jacket Material	PVC(default)/LSZH/OFNP
Insertion loss	LC \leq 0.3dB; FC \leq 0.3dB	Interchangeability	\leq 0.2dB
Return loss	LC \geq 50dB; FC \geq 50dB	Vibration	\leq 0.2dB

Operating temperature	-40~75°C	Storage temperature	-45~85°C
Fiber Grade	G652D	Fiber Grade	G657A1 is customized

Quality Certification

Quality and standards are the foundation of FiberStore. We are dedicated to providing customers with the outstanding, standards-compliant products and services.

FiberStore has passed many quality system verification, like CE, RoHS, FCC, established an internationally standardized quality assurance system and strictly implemented standardized management and control in the course of design, development, production, installation and service.

