



Conector Rápido SC/PC Simplex Monomodo



Descripción

Nombre: CONECTOR RAPIDO SC/PC SIMPLEX MONOMODO FIBRA FTTH Conector terminal o punta SC con pulido PC para fibra óptica FTTH SIMPLEX MONOMODO **Referencia:** SC/PC FAST **Marca:** VICOM **Empaque:** UNIDAD **Precio por:** Unidad **Ficha técnica:** [SC/PC FAST](#)

Información del producto

Descripción: CONECTOR RAPIDO SC/PC SIMPLEX MONOMODO FIBRA FTTH. Marca: VICOM. Referencia: SC/PC FAST Conector Rápido SC-PC Tipo Furukawa Azul, utilizado para hacer conectorizaciones en campo de cables ópticos, en redes FTTx. Diseñado para aplicación interna en áreas controladas o cajas de terminación.

Precio: \$3.570 IVA INCLUIDO

SKU: 1-3-31

Categorías: [CONECTORES](#), [CONECTORES PARA FIBRA OPTICA](#), [VICOM](#)

Etiquetas: [0010003000031](#), [1-3-31](#), [CONECTOR ÓPTICO DE CAMPO SC-UPC](#), [CONECTOR RAPIDO SC/PC SIMPLEX MONOMODO](#), [CONECTORES](#), [CONECTORES FIBRA OPTICA](#),

Fiber Optic Fast Connector

SC/APC Fiber Optic Fast Connector Specification

Product overview:
The Fast Connector (FC) is a field-installable connector for single-mode optical fiber. It is designed for use in FTTH applications. The connector is made of high-strength plastic and is designed to be installed in the field. It is designed to be installed in the field. It is designed to be installed in the field.

Specifications:

Parameter	Value	Parameter	Value
Material	PC/ABS	Temperature range	-40 to +70 °C
Length	40 mm	Temperature range	-40 to +70 °C
Width	12 mm	Temperature range	-40 to +70 °C
Height	12 mm	Temperature range	-40 to +70 °C
Weight	0.5 g	Temperature range	-40 to +70 °C
Operating temperature	-40 to +70 °C	Temperature range	-40 to +70 °C
Storage temperature	-40 to +70 °C	Temperature range	-40 to +70 °C

Operation Instructions:

Product Components:

