



## **Conector Tipo N Macho Cable Heliax 1/2 Superflex**



# Descripción

**Nombre:** CONECTOR TIPO N MACHO CABLE HELIAX 1/2 SUPERFLEX **Referencia:** NM-SF1/2

- **Tipo:** N Macho recto (Plug - Male)
- **Impedancia:** 50 Ohm
- **Rango de frecuencia:** DC-3GHz
- **Cable Compatible:** Heliax superflexible de 1/2"

**Marca:** VICOM **Empaque:** 5.5 cm **Precio por:** Unidad **Ficha técnica:** [NM-SF1/2](#) **Reporte de pruebas:** [NM-CL-1/2R](#)

## Información del producto


**Descripción:** CONECTOR TIPO N MACHO CABLE HELIAX 1/2 SUPERFLEX. Marca: VICOM. Referencia: NM-SF1/2

**Precio:** \$29.750 IVA INCLUIDO

**SKU:** 1-2-69

**Categorías:** [CONECTORES](#), [CONECTORES DE RF Y COAXIALES](#), [PRODUCTOS DESTACADOS DEL MES](#), [VICOM](#)

**Etiquetas:** [0010002000069](#), [1-2-69](#), [CABLE HELIAX](#), [CONECTOR TIPO N MACHO CABLE HELIAX 1/2 SUPERFLEX](#), [CONECTORES](#), [CONECTORES DE RF Y COAXIALES](#), [NM-SF1/2](#),

| SPECIFICATION                                                                       |                                               |
|-------------------------------------------------------------------------------------|-----------------------------------------------|
| N-STRAIGHT PLUG FOR 1/2" SUPERFLEXIBLE CABLE                                        |                                               |
|  |                                               |
| Reference                                                                           | ECI 80188-18                                  |
| Electrical                                                                          |                                               |
| Characteristic Impedance                                                            | 50 ohm                                        |
| Frequency Range                                                                     | DC-3GHz                                       |
| VSWR                                                                                | <1.10                                         |
| Dielectric Withstanding Voltage                                                     | 2500V RMS/50Hz/1min test                      |
| Dielectric Resistance                                                               | >5000MΩ                                       |
| Contact Resistance                                                                  | Center Contact <1.0mΩ<br>Outer Contact <5.0mΩ |
| Mechanical                                                                          |                                               |
| Durability                                                                          | Welding cycles 20000                          |
| Material and plating                                                                |                                               |
| Body                                                                                | Material: Brass<br>Plating: Ni or 174 alloy   |
| Insulator                                                                           | PTFE                                          |
| Center conductor                                                                    | Brass/Invar/Brass                             |
| Temperature                                                                         |                                               |
| Temperature Range                                                                   | -40°C~+85°C                                   |

